

PLATINUM SPLIT H.E.

220V Condensing Unit (Wall Mount)



FEATURES

- + Quiet and efficient operation
- + Advanced electronic control system
- + Flare fittings for easy installation
- + Standard and 24V thermostat options available.
- + 55°F temperature differential between the cellar and condensing unit air intake temperature.



UNIT SPECS

*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

EVAPORATOR					
Model	Mini		4000	8000	Twin
Cellar Size	500 cu. ft.*		1000 cu. ft.*	1750 cu. ft.*	3000 cu. ft.*
Fan Speed	Low	Medium	Single Speed	Single Speed	Single Speed
BTU/h (60°F condenser air Intake temperature) Sensible / Total	1829 / 2436	2275 / 2891	COMING SOON	4814 / 5687	COMING SOON
BTU/h (75°F condenser air Intake temperature) Sensible / Total	1760 / 2326	2127 / 2641		4455 / 4997	
BTU/h (85°F condenser air Intake temperature) Sensible / Total	1666 / 2141	2078 / 2492		4370 / 4834	
dBA	46	52		56	
Dimensions	13"L x 20"W x 10.5"H			16.1"L x 20.5"W x 15.5"H	
Refrigerant	R-134a				
Voltage Rating	120V (15-amp dedicated circuit required)				
Weight (lbs)	33		COMING SOON	54	COMING SOON
Amps	0.97 (Running Amps)			1 (Running Amps)	
Drain Line	1/2" ID clear plastic tubing (not provided)				
Installation	Evaporator unit is installed in the cellar.				
Thermostat	KDT - Advanced digital display (50-ft. cable), liquid-temperature-measuring bottle probe, 24V - customer supplied				
Temp. Delta	Can maintain a 55°F cellar temperature with up to 120°F condenser air intake temperature.				
Warranty	Two-year limited warranty (parts and labor)				

CONDENSER				
Model	Mini	4000	8000	Twin
dBA	48	48	48	48
Dimensions	31.18"L x 10.75"W x 21.18"H			
Condensing Unit HP	0.35HP	0.6HP	0.7HP	COMING SOON
Voltage Rating	220V (15-amp dedicated circuit required)			
Weight (lbs)	51		COMING SOON	61
Amps	LRA 5.3A, RLA 1.55A, FLA 1.7A			LRA 13.2, RLA 3.19, FLA 3.66
Line Set	Liquid line 1/4" OD; Suction line 3/8" OD (less than 50 ft), 1/2" (greater than 50 ft)	Liquid line 1/4" OD; Suction line 1/2" OD (less than 50 ft), 5/8" (greater than 50 ft)		COMING SOON
Installation	The condensing unit is installed up to 100 feet from evaporator unit.			
Temp. Delta	Can maintain a 55°F cellar temperature with up to 120°F condenser air intake temperature.			
Warranty	Two-year limited warranty (parts and labor)			

WWW.WHISPERKOOL.COM

| 1-800-343-9463

Rev #05252021

* DB values are tested in a controlled test chamber environment and different surface textures or items in the cellar can affect the DB rating.